



1. SURFACE OF DOOR WHERE EXIT DEVICE IS TO E APPLIED MUST BE FLUSHED.
2. SEE MASTER SHEET FOR AREAS REQUIRING REINFORCEMENTS.
3. SEE STRIKE TEMPLATE FOR TOP AND BOTTOM STRIKES.
4. WE RECOMMEND THAT ALL TAPPED HOLES BE DRILLED AND TAPPED IN FIELD.
5. TOLERANCE ON ALL DIMENSION +/- 1/64"

The illustration and technical description in this cut sheet is current as of the date in version date on the right. Cal-Royal Product reserves the right to, and may, on occasions, make changes and/or improvements in designs and dimensions without prior notice.



6605 Flotilla Street
 City of Commerce
 CA 90040 USA
 Tel:# (323) 888-6601
 FAX # (323) 888-6699
 WEB SITE:
 CAL-ROYAL.COM
 Email: sales@cal-royal.com

ITEM NO.	DESCRIPTION :
2260SVR	TEMPLATE LAY-OUT FOR 2260 SURFACE VERTICAL ROD

NOT TO SCALE
 PAGE 1 OF 1

UNIT
 PRIMARY DIMENSION SHOWN IN INCHES, DIMENSIONS IN () ARE MM

Prepared By: BBT / ADG AED / CVL

DATE: 08/28/23

DWG. NO. EDT-4084-08/23-1of1
 REV