8600 SERIES: ACCESSORIES



ACTUATORS & ACCESSORIES

PUSH PLATES 4.5" SQUARE HARD WIRED or WIRELESS





8636-SW

- 4.5 inch square stainless steel push plate
- Blue handicap logo only
- · Available in Pair, Hard Wired, Item No 8650-KIT
- Available in Pair with Wireless Radio Kit, Item No 8651-KIT
- (1) 8636-SW, Stainless steel push plate
- (1) 8636-SM, 4.5" square surface mount box

PUSH PLATES 6" ROUND HARD WIRED or WIRELESS



- 6 inch round stainless steel push plate
- Blue handicap logo
- Available in Pair, Hard Wired, Item No 8650-KIT
- Available in Pair with Wireless Radio Kit, Item No 8651-KIT
- (1) 8637-SW, 6" Stainless steel push plate
- (1) 8637-SM, 6" round surface mount box

PUSH RHR Lobby





WIRELESS RADIO KIT



- RADIO KIT eliminates the hassle of wiring from actuator to controller.
- Federal Communications Commision (FCC) Approved
- For use with 8636-SW and 8637-SW for conversion or replacement
- (1) Receiver, 433 Mhz
- (2) Transmitters, 433 Mhz

VERTICAL ACTUATOR BAR HARD WIRED OR WIRELESS



- Exceeds California Building Code Section 1117B.6
- Weather Resistant, stainless steel construction
- Membrane switches provide quite & reliable activation
- Entire surface provides activation from any angle
- Can be mounted on a wall or to a bollard
- 6" W x 36" H x 1"Thick
- ACT-36, 36" Hardwired, txt & logo • ACT-900, 36" Wireless, 900 MHz

INFRARED SAFETY SENSOR, HARD WIRED



SCAN-8660

- Low profile design reduces accidental damage
- Can be mounted horizontal or vertical
- Detects the presence of a pedestrian, while the door is opening or closing using triangulation
- · Length: 34.5 inches
- Power: 12/24 VAC / VDC
- SCAN-8660, Door Mounted, active infrared safety sensor



8600 SERIES: ACCESSORIES



ACTUATORS & ACCESSORIES

TOUCHLESS SWITCH, HARD WIRED



CTB-01

- · Touchless, wave to open switch
- Active Infrared Sensing Technology, 1"- 5" range
- 2" x 4", Stainless Steel
- · Fits in a single gang electrical box
- Power: 12/24V DC
- CTB-01, 2.75" x 4.5", 1-gang, Text, Logo & Hand

TOUCHLESS SWITCH, HARD WIRED





CTB-02

- · Touchless, wave to open switch
- Active Infrared Sensing Technology, 1"- 5" range
- 4.5" x 4.5", Stainless Steel plate with surface mount plastic box
- Power: 12/24V DC
- CTB-02, 4.5" x 4.5" Square, Text, Logo & Hand

TOUCHLESS SWITCH, HARD WIRED



CTB-05

- Infrared Photoelectric Reflective Sensor Switch
- 2"- 8" range, With Red/Green LED indicator
- Adjustable timer delay function, 0.5 to 20 sec.
- 1.5" x 4.5", Stainless Steel
- Fits in a standard jamb size electrical gang box
- Power: 12/24V DC
- CTB-05, 1.5" x 4.5", single gang, Text & Hand

TOUCHLESS SWITCH, HARD WIRED



- Infrared Photoelectric Reflective Sensor Switch
- 2"- 8" range, With Red/Green LED indicator
- Adjustable timer delay function, 0.5 to 20 sec.
- 4.5" x 4.5", Stainless Steel plate with surface mount plastic box
- Power: 12/24V DC
- CTB-07, 4.5" x 4.5" Square, Text, Logo & Hand

TOUCHLESS SWITCH, WIRELESS



- · Touchless, wave to open switch
- · Battery Powered, Active Infrared Sensing Technology, 1"-11" adjustable sensing range
- 2.4GHz Wireless Frequency
- LED Indicator, signal output for 1.5 seconds
- with built-in Radio Transmitter
- 4.5" x 4.5", Stainless Steel plate
- Sold per pair (2 Switches & 1 Receiver)
- Power: 12-30V DC
- CTB-08W, 4.5" x 4.5" Square, Text, Logo & Hand

TOUCHLESS SWITCH, WIRELESS



- · Touchless, wave to open switch
- Battery Powered, Active Infrared Sensing Technology, 1"-9" adjustable sensing range
- 2.4GHz Wireless Frequency
- with built-in Radio Transmitter
- Red/Green LED Indicator
- 4.5" x 4.5", Polycarbonate plate
- Sold per pair (2 Switches & 1 Receiver)
- Power: 12-30V AC/DC
- CTB-09W, 4.5" x 4.5" Square, Text, Logo

TOUCHLESS SWITCH, HARD WIRED









8630SW

8631SW 8632SW

- · Utilizes microwave motion technology
- 2" to 24" detection range
- Audible and visual alert indications of activation
- Power: 12/24V AC/DC
- 8630SW, 4.5" x 4.5", double gang, Text & Hand
- 8631SW, 4.5" x 2.75", single gang, Text & Hand
- 8632SW, 4.5" x 1.68", Text & Hand
- 8640-SM, double gang, surface mount box
- 8641-SM, single gang, surface mount box
- 8642-SM, 1.5" x 4.75" jamb surface mount box, Hardwired solutions only

TOUCHLESS SWITCH, HARD WIRED







- · Utilizes microwave motion technology
- Adjustable from 4" to 24" range
- Microwave cell can be mounted behind drywall
- · Comes with both single gang and double gang faceplates
- Power: 12/24V AC/DC
- 8633-SW, Microwave Cell Switch, with Single and Double gang BLACK faceplate, Text & Hand
- 8641-SM, Single gang, surface mount box
- 8640-SM, Double gang, surface mount box

TOUCHLESS SWITCH, SHORT RANGE HARD WIRED





8634-SW

8635-SW

- · Utilizes capacitance technology
- Short range detection zone reduces unwanted activations
- Touchless design reduces the spread of bacteria, disease and contamination
- Power: 12/24V AC/DC
- 8634-SW, 6" Round, Text, Logo & Hand
- 8635-SW, 4.75" Square, Text, Logo & Hand

