


# 8600 Series

Automatic "LOW ENERGY" Swing Door Operator
ANSI A156.19 Low Energy Standard, UL325 & UL991 Listed,





**UL10C Listed** for Positive Pressure Fire Test



#### **HOW TO ORDER:**

Must specify ITEM # + LENGTH + FINISH when ordering.
>> eg. 8601-39 ALUM for 8601 with 39" length in Alum finish

# STOCK ITEM SHADED IN BOLD NON-STOCK ITEMS AVAILABLE WITH FACTORY LEAD TIME AND SUBJECT TO MINIMUM ORDER

TYPE	ITEM#	# DESCRIPTION	FINISH MC	MOUNT	HANDING	TYPE OF ARM		UNIT
IIFE				MOUNT		ITEM#	Reveal	UNII
	8601	1 unit, 1 controller, 1 cover, <b>HANDED</b> Standard Length: 39" Optional Length: 45" or 51" Add \$345.52 to List Price	ALUM, DB	Push	LHR	8622-ARM	0 - 14"	
	8602				RHR	0022-ARIVI		Each
Single Operator	8603			′! -	LH	8625-LH	0 - 4"	
Sin	8604				RH	8624-RH		
	8605				LH	8626-ARM	0 - 6"	
	8606				RH			
Independent or Simultaneous Pair	8607	2 units, 2 controllers, 1 cover, <b>NON-HANDED</b> Standard Length: 75"	ALUM, DB	Push	LHR / RHR	8622-ARM	0 - 14"	
	8608			Pull	,	8625-LH & 8624-RH	0 - 4"	
	8609	Optional Length: 87" or 99"  Add \$345.52 to List Price			Pull	LH/RH	8626-ARM	0 - 6"
Double Egress Independent or Simultaneous Pair	8610	2 units, 2 controllers, 1 cover, <b>HANDED</b>	ALUM,	ALUM. Push/	LH / RHR	8625-LH & 8622-ARM	0 - 4" & 0 - 14"	Each
	8611				LHR / RH	8622-ARM & 8624-RH	0 - 14" & 0 - 4"	
	8612	Standard Length: 75" Optional Length: 87" or 99" Add \$345.52 to List Price	DB	Pull	LH / RHR	8626-ARM & 8622-ARM	0 - 6" & 0 - 14"	
	8613				LHR / RH	8622-ARM & 8626-ARM	0 - 14" & 0 - 6"	

for Optional Interior Operator, prefix "INT" before item #. (eg. 8601-39 ALUM with INT option will be "INT8601-39 ALUM)

NOTE: INTERIOR OPERATOR OPTION IS SUBJECT TO AVAILABILITY AND FACTORY LEAD TIME

#### ► PACKAGING INCLUDES

- ➤ Low Energy Unit
- Safety Signage & Guideline Sticker
- > One Arm (either Push / Pull, specify Left / Right)

#### ► STOCK FINISHES

- > Aluminum (ALUM)
- Dark Bronze (DB)
- > Consult factory for other finishes and sizes of the unit
- Price does not include Switches or Actuator







ILLUSTRATION	ITEM#	DESCRIPTION	FINISH	UNIT
	8622-ARM	Standard Push Arm, Non-Handed, for 0" to 14" reveal	ALUM, DB	Each
	8623-EXT	Optional Push Arm Extension, center arm only. Non-Handed, for 14" to 20" reveal	ALUM, DB	Each
	8624-RH	Angle Pull Arm, Right Handed, 0" to 4" reveal	_	
	8625-LH	Angle Pull Arm, Left Handed, 0" to 4" reveal	ALUM, DB	Each
	8626-ARM	Optional Straight Pull Arm, Non-Handed, for 0" to 6" reveals		
PUSH To oven	8636-SW	<ul> <li>4.5" Square Stainless Steel Push Plate with blue handicap logo</li> <li>Includes surface mounting box</li> <li>(hard wired connection)</li> </ul>		1 set
PUSH TO GREA	8650-KIT	Basic 4.5" Square Push Plate package, Includes (2) <b>8636-SW</b> (hard wired connection)		1 set
PUSH TO OPEN PUSH	8651-KIT	Basic 4.5" Square Push Plate package, Includes (2) <b>8636-SW</b> , with 1 set of <b>MTR-01</b> (wireless connection)		1 set



ILLUSTRATION	ITEM#	DESCRIPTION	FINISH	UNIT
PUSH 10 OPEN	8637-SW	<ul> <li>6" Round Stainless Steel Push Plate</li> <li>with blue handicap logo</li> <li>Includes surface mounting box</li> <li>(hard wired connection)</li> </ul>		Each
PUSH TO OPEN PISH TO OPEN	8652-KIT	Basic 6" Round Push Plate package, Includes (2) 8637-SW (hard wired connection)		Each
PUSH 10 OPEN	8653-KIT	<ul> <li>Basic 6" Round Push Plate package,</li> <li>Includes (2) 8637-SW,</li> <li>with 1 set of MTR-01</li> <li>(wireless connection)</li> </ul>		Each
Wave To Open	CTB-01	Touchless Wave to Open Switch with Text, Logo & Hand		Each
Wave To Open W	CTB-02	Touchless Wave to Open Switch with Text, Logo & Hand		Each
Wave To Open	CTB-05	Touchless Wave to Open Switch with Text & Hand • infrared photoelectric reflective sensor, 2"- 8" range • fits in a standard jamb size electrical box • 1.5" x 4.5" Stainless Steel plate • Power: 12-24V DC • weather resistant & adustable timer delay, • red / green LED indicator • (hard wired connection)		Each







ILLUSTRATION	ITEM#	DESCRIPTION	FINISH	UNIT
Wave To Open W	CTB-07	Touchless Wave to Open Switch with Text, Logo & Hand  infrared photoelectric reflective sensor, 2"- 8" range  includes surface mount plastic box  4.5" x 4.5" Stainless Steel plate  Power: 12-24V DC  weather resistant & adustable timer delay  red / green LED indicator  (hard wired connection)		Each
	CTB-08W	<ul> <li>Touchless Wave to Open Switch with Text, Logo &amp; Hand</li> <li>Kit includes:</li> <li>(2) Touchless Wireless Switch with transmitter &amp;</li> <li>(1) Receiver 2.4GHz</li> <li>battery powered, active infrared sensing technology, 1"-11" adjustable sensing range</li> <li>4.5" x 4.5" Stainless Steel plate</li> <li>Power: 12-30V DC</li> <li>LED indicator, signal output for 1.5 seconds</li> <li>(wireless connection)</li> </ul>		1 set
WAVE TO OPEN  WAVE TO OPEN  WAVE TO OPEN  WAVE TO OPEN  BOOKSHOOMS	CTB-09W	Touchless Wave to Open Switch with Text & Logo  Kit includes:  (2) Touchless Wireless Switch with transmitter &  (1) Receiver 2.4GHz  battery powered, active infrared sensing technology, 1"-9" adjustable sensing range  4.5" x 4.5" Polycarbonate plate  Power: 12-30V AC/DC  red/green LED indicator  (wireless connection)		1 set
WAVE TO  OPEN  H	8630-SW	<ul> <li>Touchless Switch (text &amp; hand)</li> <li>with microwave motion technology</li> <li>4.5" x 4.5", double gang</li> <li>2" - 24" detection range</li> <li>(hard wired connection)</li> </ul>		Each
	8640-SM	Surface Mount Box, double gang <ul> <li>can be used with 8630-SW &amp; 8633-SW</li> <li>4.5" x 4.5", square</li> </ul>		Each
WAVE TO  OPEN  H	8631-SW	Touchless Switch (text & hand)  • with microwave motion technology  • 4.5" x 2.75", single gang  • 2" - 24" detection range  • (hard wired connection)		Each



ILLUSTRATION	ITEM#	DESCRIPTION	FINISH	UNIT
	8641-SM	Surface Mount Box, single gang <ul><li>can be used with 8631-SW &amp; 8633-SW</li><li>4.5" x 2.75"</li></ul>		Each
WAVE TO  OPEN  H	8632-SW	Touchless Switch (text & hand)  • with microwave motion technology  • 4.5" x 1.68", jamb mount  • 2" - 24" detection range  • (hard wired connection)		Each
	8642-SM	Jamb Surface Mount Box • can be used with 8632-SW • 1.5" x 4.75"		Each
WAVE TO OPEN  WAVE TO OPEN  WAVE TO OPEN	8633-SW	<ul> <li>Touchless Switch (text &amp; hand)</li> <li>with microwave motion technology</li> <li>comes with both single and double gang face plates</li> <li>4" - 24" detection range</li> <li>can be used with 8640-SM &amp; 8641-SM</li> <li>(hard wired connection)</li> </ul>		1 set
WAVE TO OPEN	8634-SW	<ul> <li>6" Round Touchless Switch (text, logo &amp; hand)</li> <li>with microwave motion technology</li> <li>short range detection</li> <li>(hard wired connection)</li> </ul>		Each
WAVE TO OPEN	8635-SW	<ul> <li>4.75" Square Touchless Switch (text, logo &amp; hand)</li> <li>with microwave motion technology</li> <li>short range detection</li> <li>(hard wired connection)</li> </ul>		23011







ILLUSTRATION	ITEM#	DESCRIPTION	FINISH	UNIT
	MTR-01	Basic Radio Kit includes,  2 transmitters @ 433 MHz  1 receiver @ 433 MHz		Each
	SCAN-8660	Infrared Safety Sensor		Each
Push To	ACT-36	36" Vertical Actuator Bar with logo & text • (hard wired connection)		Each
OPEN .	ACT-900	<ul><li>36" Vertical Actuator Bar with logo &amp; text</li><li>(900 MHz wireless connection)</li></ul>		Each

