





















900 SERIES ACCESSORIES

				
900HOSPRING	900SPRING	HOSRPS / 900	SPAS900	CR900HDAR
<ul style="list-style-type: none"> • Super rigid parallel arm stopper with hold-open • Forged Steel Constructions • Non-handed • Spring loaded stop in soffit shoe • Handle controls hold-open function • Equivalent to LCN SPRING H-CUSH ARM 	<ul style="list-style-type: none"> • Super rigid parallel arm stopper • Forged Steel Constructions • Non-handed parallel arm • Spring loaded stop in the soffit shoe • Equivalent to LCN SPRING CUSH ARM 	<ul style="list-style-type: none"> • Super rigid parallel arm stopper with hold-open • Forged Steel Constructions • Non-handed with stop in soffit shoe • Handle controls hold-open function • Equivalent to LCN H-CUSH ARM 	<ul style="list-style-type: none"> • Super rigid parallel arm stopper • Forged Steel Constructions • Non-handed with stop in soffit shoe • Equivalent to LCN CUSH-N-STOP ARM 	<ul style="list-style-type: none"> • Non-handed parallel arm • Forged Steel main arm and forearm • For potentially abusive installations
				
901 / 902	RHDSA-SS	RHDSTP	945AR	900EXT
<ul style="list-style-type: none"> • Hold-open arm with parallel bracket • Forged Steel Constructions • Non-handed with stop in soffit shoe 	<ul style="list-style-type: none"> • Cushion Heavy Duty Stop Spring Arm with spring shoe • Provides a spring assisted dead stop function for regular and top jamb applications at 85°, 90°, 100°, and 110°. • Non-Handed • 0"-3 1/2" (0-89mm) Reveal • Equivalent to Dorma 8600 Series Spring Stop IS Arm 	<ul style="list-style-type: none"> • Cushion Heavy Duty Stop Arm • Provides a cushioned opening function for regular and top jamb applications at 85°, 90°, 95°, 100°, 105°, and 110°. • Non-Handed • 0"-3 1/2" (0-89mm) Reveal • Equivalent to Dorma 8600 Series Cushion IS Arm, and Norton 1600 Series 7701-CA Arm 	<ul style="list-style-type: none"> • Forged Steel main and forearm • Non-handed • Door closer arm (Main and regular forearm) 	<ul style="list-style-type: none"> • Extended long arm (3" extension) • Non-handed • For top jamb with deep reveals
				
TRACK / 900	900COV	900MET	900SMET	904
<ul style="list-style-type: none"> • Slide track arm • With removable hold-open clip • Non-handed 	<ul style="list-style-type: none"> • Full Cover • Non-handed • Plastic material 	<ul style="list-style-type: none"> • Optional full metal cover • Non-Handed • Metal material • Aluminum stock finish 	<ul style="list-style-type: none"> • Slim Cover • Non-Handed • Metal material • US32D Stainless Steel stock finish 	<ul style="list-style-type: none"> • Parallel arm drop bracket • Non-handed • Required for non-hold open parallel arm applications • To clear a surface-applied stop / holder
				
905	950	970138	970	706
<ul style="list-style-type: none"> • Parallel arm bracket • Non-handed 	<ul style="list-style-type: none"> • Flat drop bracket • Non-handed • Required for hinge mount where top rail is less than 3 1/2" • Plate requires 1 1/4" minimum head frame • Available in powder coat finishes 	<ul style="list-style-type: none"> • Sex bolts for 1 3/8" doors • Female part only • 1/4" - 20 (set of 4) • For Steel Door Application 	<ul style="list-style-type: none"> • Sex bolts • Female part only • 1/4" - 20 (set of 4) • For Steel Door Application 	<ul style="list-style-type: none"> • Thru bolts and grommet nuts • Set of 4 • For Wood and Aluminum Door Application