



ALBR6660V ADA Series (Non-Fire Rated) **ALBRF6660V ADA Series** (Fire Rated)

ADA



Vertical Rod Type Exit Device Less Bottom Rod - LBR Push Bar Exit Device / ANSI 156.3 Grade 1, 3-Hour Rated, UL-Listed ADA Compliant; Options: Alarm

ILLUSTRATION	ITEM#	DESCRIPTION	FINISHES
<u>_</u>	NON-FIRE EXIT HARDWARE		
CUL US 3 HOUR FIRE RATED UL10C, UBC7-2-1997 BESafe. Be Secure. Look for the Mark.	ALBR6660V3684	Surface vertical rod 36" X 84" *SH	US32D, ALUM, DURO
	ALBR 6680V4896	Surface vertical rod 48" X 96" *SH	
	FIRE EXIT H	ARDWARE RATED 3 HOU	RS (Includes thru-bolts)
Auxiliary Fire Latch included for fire-rated application STRIKE HOLE PLUG (for Strike Door)	ALBRF 6660V3684	Surface vertical rod 36" X 84" *SH Includes thru-bolts & AUX Latch	US32D, ALUM, DURO
	ALBRF 6680V4896	Surface vertical rod 48" X 96" *SH Includes thru-bolts & AUX Latch	
*SH Specify Left Hand Reverse (LHR) or Right Hand Reverse (RHR) for convenience.			

ACCESSORIES	
AUXFL	Additional auxiliary latch (Raw finish)

LBR FIRE-RATED DEVICES PACKAGING

- (7pcs) Thru-Bolts for Fire-Rated Devices only.
- Packed with Auxiliary Fire Spring Latch to be installed 6" from the floor in the lower part of the door
- 1 pc Strike Hole Plug for strike door.
- 4 pcs per master carton

LBR NON-FIRE RATED DEVICES PACKAGING

4 pcs per master carton

NON-STOCK FINISHES

Availability subject to minimum quantity and lead-time.
 Consult factory.

ALARM AVAILABLE

- Alarm available on Vertical Rod Exit Devices.
- Prefix NALRM before PART #.

ANTI-MICROBIAL

Available on US32D finish Only.
 Use part # ANTB-EXIT.



E31