

45-RIM & 45-SVR (Non-Fire Rated)
F45-RIM & F45-SVR (Fire Rated)
4500 Series, Crossbar Narrow Stile Exit Device
ANSI A156.3 Grade 1, 3-Hour Rated, UL-Listed



ILLUSTRATION	ITEM #	DESCRIPTION	FINISH		
<div style="display: flex; justify-content: space-around; margin-top: 10px;"> <div style="border: 1px solid black; padding: 2px; text-align: center;">LIFETIME WARRANTY</div> <div style="border: 1px solid black; padding: 2px; text-align: center;">BHMA CERTIFIED <small>Be Safe. Be Secure. Look for the Mark.</small></div> </div>	NON-FIRE EXIT HARDWARE				
	45-RIM-36	Rim exit, 36" wide, *SH	ALUM	DURO	
	45-RIM-48	Rim exit, 48" wide, *SH			
	45-SVR-3684	Surface vertical rod, 36" x 84"			
	45-SVR-4896	Surface vertical rod, 48" x 96"			
	FIRE EXIT HARDWARE RATED 3 HOURS (Includes thru-bolts)				
	F45-RIM-36	Rim exit, 36" wide, *SH	ALUM	DURO	
	F45-RIM-48	Rim exit, 48" wide, *SH			
	F45-SVR-3684	Surface vertical rod, 36" x 84"			
	F45-SVR-4896	Surface vertical rod, 48" x 96"			

*SH Specify Left Hand Reverse (LHR) or Right Hand Reverse (RHR) for convenience on RIM DEVICES ONLY.
SURFACE VERTICAL ROD (SVR) DEVICES are Non-Handed and are Easily field reversible.

❖ ❖ ❖ **MUST ORDER TRIM SEPARATELY** ❖ ❖ ❖

PACKAGING INCLUDES

- 4 pcs per master carton
- Thru-Bolts for Fire-Rated Devices only. (8pcs for Rim, 12pcs for Surface Vertical Rod)

NON-STOCK FINISHES

- Availability subject to minimum quantity and lead time. Consult factory.

QUANTITY DISCOUNT

36 UNITS MIXED - LESS 5%
72 UNITS MIXED - LESS 10%

LBR45-SVR (Non-Fire Rated)

LBRF45-SVR (Fire Rated)

4500 Series, Crossbar Narrow Stile Exit Device

Less Bottom Rod - LBR; ANSI A156.3 Grade 1, 3-Hour Rated, UL-Listed



ILLUSTRATION	ITEM #	DESCRIPTION	FINISH		
			ALUM	DURO	
	NON-FIRE EXIT HARDWARE			ALUM	DURO
	LBR45-SVR-3684	Surface vertical rod, 36" x 84"	EACH	EACH	
	LBR45-SVR-4896	Surface vertical rod, 48" x 96"	EACH	EACH	
	FIRE EXIT HARDWARE RATED 3 HOURS (Includes thru-bolts)				
	LBRF45-SVR-3684	Surface vertical rod, 36" x 84" Includes thru-bolts & AUX Latch	EACH	EACH	
	LBRF45-SVR-4896	Surface vertical rod, 48" x 96" Includes thru-bolts & AUX Latch	EACH	EACH	

SURFACE VERTICAL ROD (SVR) DEVICES are Non-Handed and are Easily field reversible.

ACCESSORIES		
AUXFL	Additional auxiliary latch (Raw finish)	EACH

❖ ❖ ❖ **MUST ORDER TRIM SEPARATELY** ❖ ❖ ❖

LBR FIRE-RATED DEVICES PACKAGING

- (10pcs) Thru-Bolts for Fire-Rated Devices only.
- Packed with Auxiliary Fire Spring Latch, to be installed 6" from the floor in the lower part of the door
- 1 pc Strike Hole Plug for strike door.
- 4 pcs per master carton

LBR NON-FIRE RATED DEVICES PACKAGING

- 4 pcs per master carton


NON-STOCK FINISHES

- Availability subject to minimum quantity and lead-time. Consult factory.

QUANTITY DISCOUNT
36 UNITS MIXED - LESS 5%
72 UNITS MIXED - LESS 10%

► **TRIMS & ACCESSORIES LIST**

All trims include 6-pin "C" keyway cylinder. Other major manufacturers' keyways available. (See below)

★ TRIMS AND ACCESSORIES ★			
ILLUSTRATION	ITEM #	DESCRIPTION	EACH FINISH
ESCUTCHEON TRIMS (Non-Handed)			
	ESC45-00 ICESC45-00 ICSCESC45-00	Clutch Entrance, key-locks or unlocks escutcheon trim - operates as classroom function ANSI FUNCTION (08)	US26D DURO
	ESC45-05 ICESC45-05 ICSCESC45-05	Clutch Storeroom, key unlocks lever, lever retracts latch bolt, otherwise always locked. ANSI FUNCTION (09)	
	ESC45-30	Passage, always operable and free. ANSI FUNCTION (14)	
	ESC45-40	Dummy Escutcheon trim. ANSI FUNCTION (02)	

STRIKES & ACCESSORIES			
ITEM #	DESCRIPTION	FINISH	UNIT
620	Top Strike	---	Each
221	Handicap Bottom Strike	---	
233	Alternate Flush Mounting Bottom Strike	---	
N251	Overlapping strike	---	
201	Shim Kit for 45-RIM & F45-RIM Exit Devices, 1/8" (Thick)	---	
212	Shim Kit for 45-SVR & F45-SVR Exit Devices, 1/8" (Thick)	---	
357	Thru-Bolts for Rim Fire and Panic Grade 1 3/4" door (6 pcs)	---	
363	Thru-Bolts for Rim Fire and Panic Grade 2 1/4" door (6 pcs)		
369	Thru-Bolts for Vertical Rod Fire and Panic Grade to be used with trim, 1 3/4" door (14 pcs)	---	
375	Thru-bolts for Vertical Rod Fire and Panic grade to be used with trim, 2 1/4" door (14 pcs)		
EXTROD66-12	12" Extension Rod	ALUM, DURO	
EXTROD66-24	24" Extension Rod		
LFF	Lock front filler (Zinc plated)	---	
SF	Strike filler (Zinc plated)	---	
CUT CHARGE	Labor for cutting exit devices to size (applicable to all Series)		
ANTB-TRIM	Anti-Microbial Coating on Exit Device Trims in US26D only		

FOR MULLIONS AND ACCESSORIES, PLEASE REFER TO PAGE E52.

- (IC) Indicates function available with **Best, Falcon & Arrow Interchangeable Core.**
- (ICSC) Indicates function available with **Schlage Full Size Format Interchangeable Core.**

●● For IC Core see pages L119 - L120.
CONSULT FACTORY OR WEBSITE FOR TEMPLATES ON ALL EXIT DEVICES AND TRIMS

◆ OTHER KEYWAYS	
ESC45-00, ESC45-05	Schlage C-K, Russwin D1, D2, D3, Corbin 60, Sargent LA-LB-LC, Falcon / Weiser E, Corbin-Russwin L4, Arrow A, Yale 8, Yale GA, Kwikset