UL Product **iQ**[™]

GWZQ7.R21764 - Door Hinges Certified for Canada

Door Hinges Certified for Canada

See General Information for Door Hinges Certified for Canada

CAL-ROYAL PRODUCTS INC

R21764

ጯ

6605 FLOTILLA ST COMMERCE, CA 90040-1815 USA Stainless steel ball bearing type hinges for use on swinging type fire doors rated up to and including 3 hours.

Models ULBB6801, ULBB6802, ULBB6803, ULBB4543, ULBB454, ULBB313, ULBB31, ULBB52454, ULBB5200, ULBB54, ULBB545, ULBB5254, ULBB5210, ULBB5500HD.

Full mortise energy transfer hinge models ELELR4, ELELR6, ELELR8, ELELR12, ELE4, ELE6, ELE8, ELE12, which can be suffixed by Model # BB5500, BB5210, BB5254, BB5200, BB52200, BB52454, BB52454, BB55, BB545, BB545, BB54, BB31, BB454, and BBSC56, rated up to and including 3 h.

CR3D62, for use on swinging type fire doors of type wood / composite type rated up to and including 2 hours with a minimum thickness of 120mm, incorporating active bolts and studs, for doors (leaf) limited to 976mm wide x 2432mm high. Refer to manufacturers installation instructions.

CR3D40, for use on swinging type fire doors of types wood / composite type rated up to and including 2 hours with a minimum thickness of 120mm, incorporating active bolts and studs, for doors (leaf) limited to 976mm wide x 2132mm high. Refer to manufacturers installation instructions.

Last Updated on 2018-09-17

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"