

GXOW.R25997 - Flush and Surface Bolts, Automatic Type

Flush and Surface Bolts, Automatic Type

See General Information for Flush and Surface Bolts, Automatic Type

CAL-ROYAL PRODUCTS INC

R25997

6605 FLOTILLA ST

COMMERCE, CA 90040-1815 USA

Models, SLAUTOFLM3, AUTOFLM1 top and bottom flush bolt units for use on metal doors measuring up to 1219 mm (4 ft) wide and 2438 mm (8 ft) high, rated up to and including 3 hrs.

Model AUXAUTOFLM1 top flush bolts only for use on metal doors measuring up to 1219 mm (4 ft) wide and 2438 mm (8 ft) high, rated up to and including 3 hrs.

Models, SLAUTOFLW4, AUTOFLW22 top and bottom flush bolt units for use on wood or plastic covered composite type fire doors measuring up to 1219 mm (4 ft) wide and 2438 mm (8 ft) high, rated up to and including 1-1/2 hrs.

Model AUXAUTOFLW22 top flush bolts only for use on wood doors measuring up to 1219 mm (4 ft) wide and 2438 mm (8 ft) high, rated up to and including 20 min.

Last Updated on 2014-08-04

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"