

GYJT7.R14738 - Single-point Locks and Latches Certified for Canada

Single-point Locks and Latches Certified for Canada

CAL-ROYAL PRODUCTS INC
6605 FLOTILLA ST
COMMERCE, CA 90040-1815 United States

R14738

Cylindrical type, Series C6N with 1/2 in. latch bolts.

Cylindrical type, Series BA with 1/2 in. (12.7 mm) latch bolt.

Tubular type, Series ULLGEN with a 12.7 mm (1/2 in.) latch bolt may be supplied with zinc levers.

Cylindrical type with 1/2 in. throw, SL Series, CSL Series, ICSL Series, ICCSL Series, AG Series, ICAG Series, ICCAG Series, BA Series, ICBA Series, PLY Series, PLSK Series, RL Series, CRL Series, ICRL Series, ICCRL Series, LX Series, TUB Series, ICCGN Series.

Mortise type: Series NM8010, NM8040, NM8050, NM8060, NM8070, NM8080, NM8453, NM8456, NM8466, NM8473, NM8485 with 3/4 in. latch throw.

Single-point locks or latches of the cylindrical type with 1/2 in. (12.7 mm) latch bolts, Models AG-00, AG-05, AG-03, AG-20, AG-30, AG-50, AG-40, AST-00, AST-05, AST-03, AST-20, AST-30, AST-50, AST-40, SG-00, SG-05, SG-03, SG-20, SG-30, SG-50, SG-40, SL-00, SL-05, SL-03, SL-20, SL-30, SL-50, SL-40, XP-00, XP-05, XP-03, XP-20, XP-30, XP-50, XP-40, PLS BRAND L-253#, PLS BRAND L-280#, PLS BRAND L-270#, PLS BRAND L-210#, PLS BRAND L-240#. ROC00, ROC05, ROC03, ROC10, ROC20, ROC30, ROC50, ROC40.

Cylindrical type, Series GRB, CAL with a 1/2 in. (12.7 mm) and 3/4 in. (19 mm) throw latch bolt for use with fire doors rated up to and including 3 hr including 20 minute wood core fire doors.

Cylindrical type, Series ICCAL with a 1/2 in. (12.7 mm) and 3/4 in. (19 mm) throw latch bolt for use with fire doors rated up to and including 3 hr including 20 minute wood core fire doors.

Cylindrical type, Series ICGRB with a 1/2 in. (12.7 mm) and 3/4 in. (19 mm) throw latch bolt for use with fire doors rated up to and including 3 hr including 20 minute wood core fire doors.

Model JHIL interconnected lock assemblies, single point lock or latch of the cylindrical type, with a 1/2 in. (12.7 mm) latch throw.

Single point locks or latches, Mortise type, Series SC with a 3/4 in. latch bolt. May be supplied with aluminum, brass, bronze, steel or stainless steel lever handles, or stainless steel push-pull trim.

Model CIL interconnected lock assemblies, single point lock or latch of the cylindrical type, with a 1/2 in. (12.7 mm) latch throw.

Models GER20, GER30, GER40, GER50, GER70, VAL20, VAL30, VAL40, VAL50, VAL70, FOR20, FOR30, FOR40, FOR50, FOR70, ATH20, ATH30, ATH40, ATH50, ATH70, JAS20, JAS30, JAS40, JAS50, JAS70, NEL20, NEL30, NEL40, NEL50, NEL70, WIL20, WIL30, WIL40, WIL50, and WIL70 tubular type single point lock with a 1/2 in (12.7mm) latch throw for use with doors rated up and including 90 minutes.

Single-point locks or latches of the mortise type with 3/4 in. latch bolts, Models CM8010, CM8044, CM8050, CM8070, CM8080, CM8060, CM8456, CM8466, CM8444, CM8453.

- With or without IC.

Last Updated on 2022-02-08

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"