



1. SURFACE OF DOOR WHERE EXIT DEVICE IS TO E APPLIED MUST BE FLUSHED.
2. SEE MASTER SHEET FOR AREAS REQUIRING REINFORCEMENTS.
3. SEE STRIKE TEMPLATE FOR TOP AND BOTTOM STRIKES.
4. WE RECOMMEND THAT ALL TAPPED HOLES BE DRILLED AND TAPPED IN FIELD.
5. TOLERANCE ON ALL DIMENSION +/- 1/64"

The illustration and technical description in this cut sheet is current as of the date in version date on the right. Cal-Royal Product reserves the right to, and may, on occasions, make changes and/or improvements in designs and dimensions without prior notice.



6605 Flotilla Street
City of Commerce
CA 90040 USA
Tel:# (323) 888-6601
FAX:# (323) 888-6699
WEB SITE:
CAL-ROYAL.COM
Email: sales@cal-royal.com

ITEM NO.	DESCRIPTION :
LBR2260SVR	TEMPLATE LAY-OUT FOR LBR2260 SURFACE LESS BOTTOM ROD

NOT TO SCALE
PAGE 1 OF 1

UNIT
PRIMARY DIMENSION SHOWN IN INCHES, DIMENSIONS IN () ARE MM

Prepared By:	BBT / ADG AED / CVL
--------------	------------------------

DATE	08/28/23
------	----------

DWG. NO.	EDT-4086-08/23-1of1
REV	