

LBR6660V (Non-Fire Rated)

LBRF6660V (Fire Rated)

Vertical Rod Type Exit Device Less Bottom Rod - LBR
 Push Bar Exit Device / ANSI 156.3 Grade 1, 3-Hour Rated, UL-Listed
 Options: Alarm



ILLUSTRATION	ITEM #	DESCRIPTION	FINISHES
<p>Auxiliary Fire Latch included for fire-rated application</p> <p>STRIKE HOLE PLUG (for Strike Door)</p>	NON-FIRE EXIT HARDWARE		
	LBR6660V3684	Surface vertical rod 36" X 84" *SH	US32D, ALUM, DURO
	LBR6680V4896	Surface vertical rod 48" X 96" *SH	
	FIRE EXIT HARDWARE RATED 3 HOURS (Includes thru-bolts)		
	LBRF6660V3684	Surface vertical rod 36" X 84" *SH Includes thru-bolts & AUX Latch	US32D, ALUM, DURO
	LBRF6680V4896	Surface vertical rod 48" X 96" *SH Includes thru-bolts & AUX Latch	

*SH Specify Left Hand Reverse (LHR) or Right Hand Reverse (RHR) for convenience.

ACCESSORIES	
AUXFL	Additional auxiliary latch (Raw finish)

❖ ❖ ❖ MUST ORDER TRIM SEPARATELY ❖ ❖ ❖

LBR FIRE-RATED DEVICES PACKAGING

- (7pcs) Thru-Bolts for Fire-Rated Devices only.
- Packed with Auxiliary Fire Spring Latch to be installed 6" from the floor in the lower part of the door
- 1 pc Strike Hole Plug for strike door.
- 4 pcs per master carton

LBR NON-FIRE RATED DEVICES PACKAGING

- 4 pcs per master carton

NON-STOCK FINISHES

- Availability subject to minimum quantity and lead-time. Consult factory.

ALARM AVAILABLE

- Alarm available on Vertical Rod Exit Devices.
- Prefix **NALRM** before **PART #**.

ANTI-MICROBIAL

- Available on US32D finish Only. Use part # **ANTB-EXIT**.