



SECURITY BOLTS				
ILLUSTRATION	ITEM	SIZE	ITEM #	FINISH
20 . · . MM	<ul> <li>Solid Brass Single Route Flush Bolt</li> <li>Designed for superior strength and smooth operation</li> <li>Individually poly-bagged</li> <li>Packed with strike and 2 sets of screws</li> <li>Architectural finishes available</li> </ul>	Dimensions Length: 7" Width: <sup>3</sup> 4" Bolt Head Diameter: <sup>5</sup> / <sub>16</sub> " Throw: <sup>3</sup> / <sub>4</sub> "	FBG6	US3, 5, 26, US26D, 15, US15A, 10B
	Strike for FBG6 and FBGEX12 Individually poly-bagged Packed with screws Architectural finishes available	Dimensions 1 ½" x <sup>5</sup> ⁄8" Screw Holes 1″ CTC	STRKFBG6	US3, 5, 26, US26D, 15, US15A, 10B
BB · · · · · · · · · · · · · · · · · · ·	<ul> <li>Solid Brass Single Route Extension Flush Bolt</li> <li>Rounded at both ends</li> <li>Designed for superior strength and smooth operation</li> <li>Individually poly-bagged</li> <li>Packed with strike and 2 sets of screws</li> <li>Architectural finishes available</li> </ul>	Dimensions Length: 7 ½" Width: ¾" Bolt Head Diameter: <sup>5</sup> /16" Throw: ⅛" Rod Length: 18"	FBGEX12	US3, 5, 26, US26D, 15, US15A, 10B
·	<ul> <li>Flip Style Mortise Flush Bolt</li> <li>Designed for superior strength and smooth operation</li> <li>Individually poly-bagged</li> <li>Packed with strike and 2 sets of screws</li> <li>Architectural finishes available</li> </ul>	Dimensions Length: 7" Width: 34" Throw: 34" Strike 1 ½" L x 5%" W	FLPFB400	US3,US5, US10B, 15, US15A, 26, US26D
2 Date of the second se	<ul> <li>Flip Style Mortise Flush Bolt with 18" Extension Rod</li> <li>Designed for superior strength and smooth operation</li> <li>Individually poly-bagged, packed per pair</li> <li>Packed with strike and 2 sets of screws</li> <li>Architectural finishes available</li> </ul>	Dimensions: Length: 7 <sup>7</sup> /16" Width: 34" Throw: <sup>11</sup> /16"; Strike 1 ½" L x 5%" W	EXTFB-1	US3,US5, US10B, 15, US15A, 26, US26D
R THEN S	<ul> <li>Solid Brass Single Route Flush Bolt</li> <li>Designed for superior strength and smooth operation</li> <li>Deep cup finger hole and double action spring combine to assure ease of operation and automatic holding of bolt in either projected or retracted position</li> <li>Includes strike and screws</li> <li>Architectural finishes available</li> <li>able for submittal purposes at www.cal-roya</li> </ul>	Dimensions Length: 6 ¾" Width: ¾" Bolt Head Diameter: <sup>5</sup> /16" Throw: <sup>3</sup> /4"	ZDFB800	US3, 5, US26, 26D, US15, 10B

