


SECURITY BOLTS

ILLUSTRATION	ITEM	SIZE	ITEM #	FINISH
	UL Listed Heavy Duty Commercial Surface Bolts <ul style="list-style-type: none"> Offers tamper-resistant mounting Can be used for both in-swinging and out-swinging doors Available with both mortise and versal strikes Conforms to ANSI / BHMA A156.16, L04161 	Dimensions: Length: 8"; Width: 3/4" Projection: 1 5/16" Bolt Throw: 1"	UL831 (ESBUL50 before)	US26D
		Dimensions: Length: 12"; Width: 3/4" Projection: 1 5/16" Bolt Throw: 1"	UL831-12 (ESBUL12 before)	
	UL Listed Solid Brass Lever Extension Flush Bolt <ul style="list-style-type: none"> Non-handed UL Listed for fire-rated metal doors 5/8" Throw Bolt tip is 1/2" Diameter Conforms to ANSI / BHMA A156.16, L04081 Optional Rod lengths available: 12", 18", 24", 36", 48" Architectural finishes available 	Body: Length: 6 3/4"; Width: 1" Depth: 1 1/4" Guide: Length: 2"; Width: 1" Thickness: 5/64" Strike: Length: 2 1/4"; Width: 15/16" Thickness: 3/32" Rod: 1/4" - 20 Threaded	MF6341	US3, 4, 5, US10, 10B, US15, 15A, US26, 26D, L1
	Strike for MF6341 <ul style="list-style-type: none"> Individually poly-bagged Packed with screws Architectural finishes available 	Dimensions: 2 1/4" x 15/16" Thickness: 3/32" Screw Holes: 1 5/8" CTC	STRKMF	US3, 10B, US15, 26, US26D
	UL Listed Solid Brass Lever Extension Flush Bolt <ul style="list-style-type: none"> Commercial Type 5/8" Throw Especially designed for wood or composite doors Conforms to ANSI / BHMA A156.16, L04081 Architectural finishes available 	Body: Length: 6 3/4"; Width: 1" Depth: 1 1/4" Guide: Length: 2 1/2"; Width: 1" Thickness: 5/64" Strike: Length: 2 1/4"; Width: 1" Thickness: 5/64"	WF6341	US3, 10B, US26, 26D, US15, US1
	Stainless Steel, UL Listed Flip Style Mortise Flush Bolt <ul style="list-style-type: none"> Non-Handed UL Listed No. R14281 Bolt tip is 1/2" Diameter 3/4" Throw Conforms to ANSI / BHMA A156.16 Optional Rod lengths available: 12", 18", 24", 36", 48" 	Body: Length: 6 3/4"; Width: 1" Depth: 1" Guide: Length: 2"; Width: 1" Thickness: 1/16" Strike: Length: 2 1/4"; Width: 7/8" Thickness: 1/16" Rod: 12" from center of flush bolt to the tip of the bolt	FBS-100	US32D, US10B, US1
	Stamped Brass Commercial Manual Flush Bolt <ul style="list-style-type: none"> Non-Handed Stamped Brass Design Bolt tip is 1/2" Diameter Optional Rod lengths available 18", 24", 36", 48" Architectural finishes available 	Body: Length: 6 3/4"; Width: 1" Depth: 1 1/4" Guide: Length: 2"; Width: 1" Thickness: 5/64" Strike: Length: 2 1/4"; Width: 1" Thickness: 5/64"	SBFB825	US3, 10B, US15, 26D