CR801 / 801S ACCESSORIES



| | | | | | í. | | |
|---|---|--|--|---|---|---|---|
| | | | Contraction of the second seco | | C | | 0 |
| 900HOSPRING | 900HOSPRING 900SPRING | | HOSRPS / 900 | | SPAS900 | | CR900HDAR |
| Super rigid parallel arm stopp with hold-open Forged Steel Constructions Non-handed Spring loaded stop in soffit sh Handle controls hold-open function Equivalent to LCN SPRING H-CUSH ARM | Super rigid parallel arm stopper Forged Steel Constructions Non-handed parallel arm Spring loaded stop in the soffit shoe Equivalent to LCN SPRING CUSH ARM | | Super rigid parallel arm stopper with hold-open Forged Steel Constructions Non-handed with stop in soffit shoe Handle controls hold-open function Equivalent to <i>LCN H-CUSH</i> <i>ARM</i> | | Super rigid parallel arm stopper Forged Steel Constructions Non-handed with stop in soffit shoe Equivalent to <i>LCN CUSH-N-STOP ARM</i> | | Non-handed parallel arm Forged Steel main arm and forearm For potentially abusive installations |
| | | | | | | action to the | Per |
| 901 / 902 | 01 / 902 RHDSA-SS | | RHDSTP | | 945AR | | 900EXT |
| Hold-open arm with parallel bracket Forged Steel Constructions Non-handed with stop in soffit shoe | Spring Arm with spring Provides a spring ass stop function for regul jamb applications at 8 100°, and 110°. Non-Handed 0"-3 ½" (0-89mm) Re Equivalent to <i>Dorma</i> | | | Cushion Heavy Duty Stop Arm Provides a cushioned opening function for regular and top jamb applications at 85°, 90°, 95°, 100°, 105°, and 110°. Non-Handed 0"-3 ½" (0-89mm) Reveal Equivalent to <i>Dorma 8600</i> <i>Series Cushion IS Arm, and</i> <i>Norton 1600 Series 7701-CA</i> <i>Arm</i> | | Steel main arm and nded bser arm (Main and forearm) | Extended long arm (3" extension) Non-handed For top jamb with deep reveals |
| | | | | 00 | | | |
| TRACK / 900 | 904 | 904 | | 905 | | 801SCOV | 801COV |
| Slide track arm With removable hold-open cli Non-handed | Non-handed Required for non-hold parallel arm application | Required for non-hold open parallel arm applications To clear a surface-applied | | Parallel arm bracket Non-handed | | ver nded Material | Full Cover Non-handed Plastic Material |
| | | | | | N. | A REAL PROPERTY OF | |
| 850S | 850W | | 850F | 970138 | } | 970 | 706 |
| | Wide Flat drop bracket Non-handed Son-handed | | | | / .) | Sex bolts Female part only '¼" – 20 (set of 4) for Steel Door Application | Thru bolts and grommet nuts Set of 4 for Wood and Aluminum Door Application |

